

GARDENING - SORTED BY POPULARITY

ATTACHMENT	PART #	APPLICATION INFO	COMPATIBILITY / ACCESSORIES	LIST PRICE
Rear Tine Tiller 	18": 92191215 20": 92191216 26": 92191217 30": 92191218 33": 921C0101 33" HD: 921C0001	BCS's most popular attachment. Bust sod, prepare seedbeds, precision cultivate, and more. 33" tillers only for 750. HD version has thicker/wider tines with heavier duty gearbox than standard 33" version.	All models, see Compatibility Charts for sizes. No accessories required.* 33" HD Tiller requires 3-stud 750 Bushing for model 750 (922C0058).	18": \$555 20": \$670 26": \$735 30": \$795 33": \$1310 33" HD: \$1540
Rotary Plow 	92191306	Break new ground, loosen up to 12" of soil on the first pass! Create raised garden beds, drainage swales, hill crops, power compost cover crops. Discharges soil to the right side only. 4 spiral blades spin at 250 RPMs on vertical shaft.	Models 732 and up. Requires Rotary Plow Wheel Extensions (part # 92243622) * Minimum of 5"x10" wheels recommended.	\$1440
Power Harrow 	21": 921PH210 32" 921PH320	Final seedbed prep tool. Not to be used for breaking new ground. Vertical tines "stir" the soil and rear mesh roller gently presses the soil for level, ready-to-plant seedbeds. "Josephine Lever" quickly drops roller into transport mode for easier maneuvering and turning at the end of the row.	21": Models 722 and up. 32": Models 739 and up. Recommended for 749 / 853 / 750 because of larger 12" wheels (more engine ground clearance). QH Bushing required.* 922WEIGHT KIT required for balance.	21": \$2100 32": \$2300
Swivel Rotary Plow 	92191308	Similar to Rotary Plow, but has two plow shares to discharge soil to either the right OR left side. A better choice for building beds on hillsides or in tight spaces. Plow share is easily selected by lever on rear of implement.	Models 739 and up, although much better for 749/853/750. 922WEIGHT KIT required for balance. Requires 3-stud 750 Bushing for model 750 (922C0058).	\$2140
NEW! Plastic Mulch Layer 	921ML001	4-foot version lays plastic over 30" raised beds or flat beds up to 36" wide. Plastic helps extend the growing life of the crop and helps reduce weed maintenance. Performs differently in various soil types. Drip tape kit available if needed. Includes Quick Hitch mounting hardware.	Models 749 and up. REQUIRED: 22"Wheel Ext. (922EX220) Plastic Mulch Roll (922PM424) Recommended accessories on pricing pages.*	\$845 See pricing pages for accessory prices.

* 750 Bushing (922C0071) required for model 750

DRAG IMPLEMENTS - SORTED BY POPULARITY

ATTACHMENT	PART #	APPLICATION INFO	COMPATIBILITY / ACCESSORIES	LIST PRICE
Root Digger 	92146340	Also called the Potato Digger, it's used to harvest small-scale crops of root vegetables. Note that it can only burrow into the soil as deeply as the soil has been previously worked.	Models 732 and up. Requires Tool Carrier Kit* (922TCK00) AND Wheel Weights / Wheel Weight Hangers.	\$115 See pricing pages for accessory prices.
Ridger 	DMW002AD	Creates hills and furrows in previously worked soil similar to Hiller/Furrower, but attaches via Tool Carrier Kit. Commonly purchased in sets of 2 to be used with the Straight Bar for dual Ridgers.	Models 722 and up. Requires Tool Carrier Kit * (922TCK00) AND Wheel Weights / Wheel Weight Hangers.	\$95 See pricing pages for accessory prices.
V-Cultivator 	DMW005D	Also called a Spring Tine Cultivator, the bars narrow or widen up to 31" with five adjustable teeth positions. Great for weed control in between crops. Includes transport/depth gauge wheel.	Models 722 and up. Requires Tool Carrier Kit (922TCK00). *	\$349 See pricing pages for accessory prices.
Moldboard Plows 	Single: 92190799 Swivel: 92190797 Model 750: 92149992	Traditional bottom plows turn over topsoil and speeds weed/crop decomposition. At least one pass with the tiller is needed prior to planting. Rotary Plow is a much better solution in most cases.	Models 749 and up. Requires Wheel Weights / Wheel Weight Hangers.	Single: \$299 Swivel: \$399 Model 750 Version: \$409
NEW! Subsoiler 	922SS000	Intended to break up or loosen soil without turning the soil over. Improves drainage, increases soil capacity for air and water, promotes deeper penetration of plant roots.	Models 749 and up. Requires Tool Carrier Kit * (922TCK00) AND Wheel Weights / Wheel Weight Hangers.	\$180 See pricing pages for accessory prices.
Tool Carrier Kit Accessory 	TOOL CARRIER KIT REQUIRED!			
<i>Empty Tang (92257851) not included as shown.</i>	<p>The Tool Carrier Kit (922TCK00) is mounted to the tractor's PTO connection point. It features an Adjustable Tool Carrier for flexibility.</p> <p>IT IS REQUIRED FOR THE IMPLEMENTS LISTED ON THIS PAGE.</p> <p>If the customer already has a Tool Carrier that previously mounted to the tractor hitch, they only need to purchase Draw Bar 922DBH00.</p>			Tool Carrier Kit: \$170 Draw Bar Only (922DBH00): \$45

* 750 Bushing (922C0071) required for model 750

MOWING - SORTED BY POPULARITY

ATTACHMENT	PART #	APPLICATION INFO	COMPATIBILITY / ACCESSORIES	LIST PRICE
Sickle Bar Mower 	Bar Assemblies: 30": 92190978 40": 92190979 45": 92190980 53": 92190981 Short Transmission (710-718): 92191994 Long Transmission (722 and Up) 92191242	A BCS original. Like a hedge clipper at ground level, it cuts material at its base and leaves it intact. Better than Dual Action bars w/ Fingers for mowing woody saplings up to 1.5" thick. Quality of cut is diminished when operating in 3rd gear. Dry "greaseable" transmissions no longer available, Oil Bath is much more durable.	All models, see Compatibility Charts for sizes. No accessories required. * Sickle Bar Weight Kit (922C0350) available for large models (especially 750) to offset engine weight.	<i>Includes price of Oil Bath Transmissions</i> 30": \$1255 40": \$1330 45": \$1385 53": \$1460
Brush Mower 	21": 92191225 26": 92191226 32": 92191229	Floating deck, two swinging blades, and heavy duty gearbox make it a reliable and economical choice for mowing heavy brush. Produces a coarse cut and the skids are non-adjustable at 4" cutting height.	Models 718+, see Compatibility Charts for sizes. Accessories may be required depending on tractor model.	21": \$1049 26": \$1079 32": \$1199
Flail Mower 	24": 92191238 30": 92191237 35": 92191239	Heaviest-duty mower in BCS fleet. Like a shredder on wheels, dozens of vertically rotating 'Y' blades pulverize plant material into a fine pulp and spread evenly across the mowing width. Crank handle infinitely adjusts cutting height control from 0.5" to 4". Caster wheels provide easy maneuverability.	Models 722+, see Compatibility Charts for sizes. No accessories required. * Scoop Blade Kits available for mowing lawns. Full-Length Rollers available. Weight Kit available for steep slopes.	24": \$2115 30": \$2195 35": \$2295
RollerBlade Flail Mower 	30": 921C0977	Like the Flail Mower, but has a lower dome and thicker, wider blades. Full length roller with crank handle infinitely adjusts height from 0.5" to 2.5". Perfect for market farmers who mow cover crops. 30" version only.	Models 739 and up. No accessories required. *	30": \$2195
Dual Action Sickle Bar Mower with Fingers 	Bar Assemblies: 47": 92190883 59": 92190879 71": 92190881 Transmission: 92191241	Formerly known as "duplex"- double reciprocating blades. Compared to standard sickle bar, it reduces vibration and enables mowing in faster speeds but not as good for mowing woody saplings because fingers are prone to breakage.	Models 722 and up, see Compatibility Chart for Sizes. No accessories required. *	<i>Includes price of Oil Bath Transmissions</i> 47": \$2064 59": \$2274 71": \$2504

* 750 Bushing (922C0071) required for models 750 / 660

MOWING (CONTINUED)- SORTED BY POPULARITY

ATTACHMENT	PART #	APPLICATION INFO	COMPATIBILITY / ACCESSORIES	LIST PRICE
NEW! Dual Action Sickle Bar Mower 	Bar Assemblies: 51": 92191269 67": 92191268 82": 92191267 Transmission: 92191241	Double reciprocating blades, compared to standard sickle bar, reduces vibration and enables mowing in faster speeds. Suitable for mowing woody material up to 0.5" in diameter. Self-adjusting tensioners minimize maintenance.	Models 732 and up, see Compatibility Charts for sizes. No accessories required. * 82" width for 660 Hydrostatic Only.	<i>Includes price of Oil Bath Transmissions</i> 51": \$2309 67": \$2569 82": \$2994 (for 660 only)
Lawn Mower 	22": 92191219 38": 92191236	Bag or side discharge. All-gear driven with heat-treated steel shafts and gears. 38" is more popular with 4-bushel bag. Top mounted lever easily adjusts twin blade height from 2.5" to 4". Convenient bag dump feature.	22": 718 and up. 38": 739 and up. PTO extensions and OH bushing required for 38" model. * Models with three working gears highly recommended.	22": \$845 38": \$2499
HD Combo Mower 	30": 92191235	30" fixed blade, floating deck, and two caster wheels. Hybrid mower intended to mow lawn and brush. Performance not as good as attachments dedicated to lawn or brush. Blade height adjusted via spacers on the blade.	Models 739 and up. No accessories required. * Swing Blade Kit available (59258015)	30": \$1445
NEW! Hay Rake 	60": 921HR060	Quickly rake 5' wide swath of grass into windrows. 8 sets of 4-tooth combs rotate on heavy duty belts to rake hay, grasses, and other plant materials for easy collection. A nice complement for the Sickle Bar / Dual Action mowers. Two wheels controlled by steering lever.	Models 722 and up. No accessories required. *	60": \$2450
Mowing Sulky 	92190569	Allows operators to ride while they mow! Mounts to tractor via extensions bolted to the wheels. With two pins, sulky can be quickly removed in the field when you encounter steep slopes or tight areas. Can only be used in front-mount (mowing) mode.	Models 722 and up. No accessories required.	\$750

* 750 Bushing (922C0071) required for models 750 / 660

SNOW REMOVAL - SORTED BY POPULARITY

ATTACHMENT	PART #	APPLICATION INFO	COMPATIBILITY / ACCESSORIES	LIST PRICE
Snow Thrower 	24": 92191223 28": 92191224	Nicknamed the "Snow Cannon!" Impeller speed of 1200 RPMs discharges wet, dry, and icy snow up to 25 feet. Stainless steel discharge chute reduces friction and prevents rust. Handle at operator's position pivots the chute. All gear drive means it outperforms belt-driven 2-stage units.	24": 710 9HP and up 28": 722 and up May require Quick Hitch, PTO Extension, or Snow Thrower Weight Kit if climbing slopes.*	24": \$945 28": \$995
Power Sweeper 	30": 92190890 40": 92190889 48": 92190893	While sweeping up to 6" of dry snow, the Sweeper can also be used for sweeping debris, dethatching, and more. The angle can be adjusted into three different settings from the operator's position and the height is adjustable via two caster wheels.	30": All models. 40": 722 and up. 48": 732 and up. No accessories required.* Wire Brush Kits available for asphalt prep.	30": \$1725 40": \$1940 48": \$2090
Snow Blade 	92191234	With a 40" width, it has a curved design to roll snow without sticking and a side-to side float that maintains full contact with the ground. Five different settings available, adjusted by handle at operator's position. Adjustable skids enable the blade to plow without removing loose gravel from driveway.	Models 722 and up. No accessories required. Weights and non-metal edge also available. Needs Empty Tang (92257851) for Quick Hitch *	\$825
NEW! Two-Stage Snow Thrower 	28": 921ST028 33": 921ST033	Best for heavy snow applications--16" or more. The unit is very well built, with 3/8" thick steel, double shear pins, and cast iron gearbox. Intended for commercial applications.	28": 739 and up 33": 749 and up No accessories required.*	28": \$1950 33": \$2095

* 750 Bushing (922C0071) required for models 750 / 660

MORE TOOLS - SORTED BY POPULARITY

ATTACHMENT	PART #	APPLICATION INFO	COMPATIBILITY / ACCESSORIES	LIST PRICE
 Chipper/Shredder	92190791	Efficiently chips limbs up to 3" thick with its 37-lb flywheel and high carbon steel blade. The all-purpose shredder has 28 swinging flails. Standard equipment includes discharge screen and set of rods-and-rollers (to process wet material). Two caster wheels for easy maneuverability.	Models 722 and up No accessories required.* Additional screen sizes also available.	\$1649 \$2049 for stand-alone unit with Subaru EX27 engine (same specs as the attachment version for BCS tractors).
 Utility Trailer	92148701	Can only be operated in "rear-mount" mode. Hauls up to 875 pounds and 16 cubic feet. 45" base wheel width. Foot and parking brakes. Easy-to-use dump and swinging tailgate.	Models 722 and up. Requires Curved Coupler: 92259500 (739 and below) 92247720 (749 and up)	\$1270
 Buddy Cart	92193040	Hauls 450 pounds and 10 cubic feet. Easily fits through common gates. Heavy duty steel tongue is spring loaded for "flex" along ground contours. Features a low center of gravity and dump lever.	Models 722 and up. No accessories required. Needs Empty Tang (92257851) for Quick Hitch *	\$560
 Dozer Blade	92190735	Can push or pull gravel, sand, dirt, and other loose material. Connects at the PTO and can be set at five different angles. 3/8" thick steel. 36" wide and 12" tall. Not for snow removal.	Model 722 and up. Commonly requires Wheel Weights / Hangers for traction. Needs Empty Tang (92257851) for Quick Hitch *	\$540
 NEW! Dethatcher	921DT000	Front-mount implement has 26" working width. Three vertically rotating shafts each with 16 free-swinging, spring-loaded blades. Articulates at the PTO connection point for uneven terrain, and includes built-in Quick Hitch tang. Full length roller in the rear adjusts depth. Great for landscapers!	Models 732 and up. Quick Hitch Bushing required *	\$1700
 NEW! Hi-Pressure Irrigation Pump	921RMIP0	Self-priming pump delivers 85 PSI and 145 GPM with 150 feet of head. Complete with 2" fittings, 50' discharge hose, 25' intake hose, foot valve, and balance wheel. Better for irrigation applications than Water Transfer Pump (see pg. 38)	All models. No accessories required.*	\$999

* 750 Bushing (922C0071) required for models 750 / 660

MORE TOOLS - SORTED BY POPULARITY

ATTACHMENT	PART #	APPLICATION INFO	COMPATIBILITY / ACCESSORIES	PRICE
Log Splitter 	921LS416	High quality, self-propelled unit is manufactured by Wallenstein. The two-stage hydraulic pump has 20 tons of pressure. Can be operated horizontally or vertically. Splits logs up to 24" long.	Models 722 and up. Required Curved Coupler: 92259500 (739 and below) 92247720 (749 and up) * 4-Way Wedge (W4120) also available.	\$2125 Power Cradle: \$249*
Pressure Washer 	3600 PSI: 92135G36 4000 PSI: 92140G40	Pump is made by AR, which offers 5-year warranty. Unit comes with 50' hose, 36" pistol-style wand, and five tips for varying angle output. Swiveling caster wheel for easy transportation to the job site. Features 16,000 cleaning units (PSI x GPM).	3600 PSI: 722 and up 4000 PSI: 732 and up Soap Injector Kit available (85.400.001)	3600: \$969 4000: \$999 Power Cradle \$249*
NEW! Water Transfer Pump 	921WP147	50 PSI and 147 GPM, this self-priming pump is fully capable of handling lawn and garden watering, flood water removal, and pond/pool filling. Includes 25' suction and 50' discharge hoses with 2" aluminum cam lock fittings, and foot valve/strainer combo to keep out large debris.	All models.*	Water Transfer Pump: \$699 Power Cradle \$249*
Power Cradle Accessory 	POWER CRADLE REQUIRED! The Power Cradle (92257880K) increases the BCS tractor's PTO speed from 990 to 3600 RPMs. IT IS REQUIRED FOR THE IMPLEMENTS LISTED ON THIS PAGE. Please note that the Power Cradle is a zero margin item for BCS America and its dealers to maintain competitive pricing.			\$249

* NOTE: Only one Power Cradle needs to be purchased to power any of the attachments that require it.

* 750 Bushing (922C0071) required for models 750 / 660